
6A 3Quadrants TRIACs

Product Summary

Symbol	Value	Unit
$I_{T(RMS)}$	6	A
V_{DRM} V_{RRM}	600/800	V
V_{TM}	1.55	V



TO-252

Features

With high ability to withstand the shock loading of large current, Provide high dv/dt rate with strong resistance to electromagnetic interference.

Application

Power charger, T-tools, massager, solid state relay, AC Motor speed regulation and so on.


Absolute maximum ratings (Ta=25°C unless otherwise noted)

Parameter	Symbol	Value		Unit
Repetitive peak off-state voltage	V_{DRM}	600/800		V
Repetitive peak reverse voltage	V_{RRM}	600/800		V
RMS on-state current	$I_{T(RMS)}$	6		A
Non repetitive surge peak on-state current (full cycle, F=50Hz)	I_{TSM}	60		A
I^2t value for fusing (tp=10ms)	I^2t	21		A^2S
Critical rate of rise of on-state current (I_G =2 x I_{GT})	dI_T/dt	I - II -III	50	A/μs
Peak gate current	I_{GM}	4		A
Average gate power dissipation	$P_{G(AV)}$	1		W
Junction Temperature	T_J	-40~+125		°C
Storage Temperature	T_{STG}	-40 ~+150		°C

Electrical characteristics (T_A=25°C, unless otherwise noted)

Parameter	Symbol	Test Condition		Value			Unit
				TW	SW	CW	
Gate trigger current	I_{GT}	V_D=12V,R_L=30Ω Tj=25℃, Fig.6	Ⅰ-Ⅱ-Ⅲ	≤5	≤10	≤35	mA
Gate trigger voltage	V_{GT}		Ⅰ-Ⅱ-Ⅲ	≤1.3			V
Non-triggering gate voltage	V_{GD}	V_D=V_{DRM} Tj=125℃		≤0.2			V
Holding current	I_H	I_T=100mA,Fig.6		≤10	≤15	≤35	mA
Latching current	I_L	IG=1.2IGT, Fig.6	Ⅰ-Ⅲ	≤10	≤25	≤50	mA
			Ⅱ	≤15	≤30	≤60	
Critical-rate of rise of commutation voltage	dV_D/dt	V_D=67%V_{DRM}, Tj=125℃		≥20	≥40	≥400	V/μs
STATIC CHARACTERISTICS							
On-state Voltage	V_{TM}	I_{TM}=8.5A,tp=380μs,Fig.4		≤1.55			V
Repetitive Peak Off-State Current	I_{DRM}	V_D=V_{DRM}= V_{RRM}	Tj=25℃	≤10	≤10	≤10	μA
Repetitive Peak Reverse Current	I_{RRM}		Tj=125℃	≤1	≤1	≤1	mA
THERMAL RESISTANCES							
Ihermal resistance	$R_{th\ (j-c)}$	Junction to case		TYP.	2.1		℃/W
	$R_{th\ (j-a)}$	Junction to ambient		TYP.	70		℃/W

Ordering Information



Typical Characteristics

FIG.1: Maximum power dissipation versus RMS on-state current (full cycle)




FIG.2: RMS on-state current versus case temperature (full cycle)




FIG.3: Surge peak on-state current versus number of cycles




FIG.4: On-state characteristics (maximum values)




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width tp < 10ms






FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature (typical values)



Marking Diagram




Ordering information

Model name	Package	Unit Weight	Base Quantity	Packing Quantity
BTB06D	TO-252	0.011oz(0.32g)	3000pcs/reel	6000pcs/box 30000pcs/Carton

Package Dimensions

TO-252



Dim	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	2.20	2.50	0.087	0.098
A1	0.00	0.12	0.000	0.005
A2	2.20	2.40	0.087	0.094
B	0.95	1.55	0.037	0.061
b	0.50	0.80	0.020	0.031
b1	0.60	0.90	0.024	0.035
c	0.40	0.60	0.016	0.024
c1	0.40	0.60	0.016	0.024
D	6.35	6.65	0.250	0.262
D1	5.20	5.40	0.205	0.213
E	5.80	6.40	0.228	0.252
e	2.20	2.40	0.087	0.094
e1	4.40	4.80	0.173	0.189
L	10.00	11.00	0.393	0.433
L1	2.70	3.50	0.106	0.138
L2	1.40	1.80	0.055	0.071
L3	0.90	1.50	0.035	0.059

Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website https://www.yfwdiode.com, or consult YFW sales office for further assistance.